

Duraline®

Heavy-Duty Lighting Streamer



Duraline has been manufacturing quality Lighting Streamers for over **50 Years**. Our **Heavy-Duty Lighting Streamer** is the mainstay of our lighting line.

Heavy-Duty Lighting Streamers provide safe overhead temporary lighting and come ready to hang. Sockets are spaced at 10 ft intervals with a 5 ft lead and tail and are ruggedly constructed and integrally molded in Hypalon rubber to either a #14 or #12 AWG three conductor heavy-duty SOW-A cable. **Heavy-Duty Lighting Streamers** can be supplied with factory installed NEMA male and female plugs. Incandescent or fluorescent medium based lamps can be used (100 Watt max). Lamps are sealed by a rubber "O" ring molded into each socket. This "O" Ring forms a watertight seal around the neck of each bulb eliminating problems associated with oil, dirt and moisture. Each socket is equipped with an external grounding ring, internal crushproof steel reinforcing ring and a heavy-duty brass grommet for quick and convenient installation.

Duraline's Heavy-Duty Lighting Streamers are your best choice for durable, long lasting, reusable lighting in abusive indoor / outdoor environments.

Each streamer socket may be protected by one of two available heavy-duty guards (optional). You may choose from either a red vinyl coated steel guard or a crushproof clear lexan guard.

Duraline Lighting Systems are Factory Mutual Approved, exceed O.S.H.A. requirements, and are suitable for IEC Class IP67 and NEMA Class 6 applications.

Duraline Div of J.B. Nottingham & Co., Inc. 75 Hoffman Lane, Islandia, NY 11749
Phone 631-234-2002 Fax 631-234-2360 Web Site <http://www.jbn-duraline.com>

Part Number	Length	No. of Lamps	Cable Size	NEMA Plug Type
M107654	50	5	12/3	5-15
M107622	50	5	12/3	None
M107656	100	10	12/3	5-15
M107669	100	10	12/3	None
M107655	50	5	14/3	5-15
M107658	50	5	14/3	None
M107657	100	10	14/3	5-15
M107659	100	10	14/3	None
M107615	500	50	12/3	None
005061	Red Vinyl Coated Steel Guard (300 Watt Max)			
004059	Lexan Crush Proof Guard (100 Watt Max)			

For all other cable sizes, lengths, plugs or socket spacing, contact a factory representative. Also available in Multi-Phase 4 and 5 wire configurations.

**Heavy-Duty Brass Mounting Grommet
For Quick Convenient Hanging**

**Solid Hypalon Rubber Molded
Construction With No Voids Or Air-Gaps**

**Structural Integrity Of Cable Is Not
Disturbed By Cutting Or Splicing**

**Cable Is A Heavy-Duty SOW-A
Type**

**Assembly Is Integrally
Molded To Cable**

**Brass External Grounding
Ring For Use With Metal
Guards**

**Durable Non-Phenolic Insulator
Reduces Moisture Absorption**

**Steel Reinforcing Ring For
Additional Crush Resistance**

**Nickel Plated Copper Alloy
Screw Shell For Increased
Protection From Elements**

Lamp Neck "O" Ring Seal

